

D		L		dk	k	dm			
RIVET SIZE	PART NUMBER	RIVET LENGTH	GRIP RANGE	HEAD DIA	HEAD HEIGHT	MANDREL DIA	HOLE SIZE(DRILL)	Shear (N)	Tensile (N)
		[+1/-0]	MIN-MIX		MAX.	MAX.	Φ	MIN.	MIN.
3.0 +0.08 -0.15	BBC3006	6.0	1.0-3.5	5.4-6.3	1.3	2.10	3.1-3.2	1800	2200
	BBC3008	8.0	3.5-5.0						
	BBC3010	10.0	5.0-7.0						
	BBC3012	12.0	7.0-9.0						
	BBC3014	14.0	9.0-11.0						
	BBC3016	16.0	9.0-12.5						
	BBC3018	18.0	12.0-14.5						
BBC3020	20.0	13.0-16.5							
3.2 +0.08 -0.15	BBC3206	6.0	1.0-3.5	5.8-6.3	1.3	2.10	3.3-3.4	1900	2500
	BBC3208	8.0	3.5-5.0						
	BBC3210	10.0	5.0-7.0						
	BBC3212	12.0	7.0-9.0						
	BBC3214	14.0	9.0-11.0						
	BBC3216	16.0	9.0-12.5						
	BBC3218	18.0	12.0-14.5						
	BBC3220	20.0	13.0-16.5						
BBC3225	25.0	15.0-21.5							
4.0 +0.08 -0.15	BBC4006	6.0	1.0-3.0	6.9-7.5	1.7	2.60	4.1-4.2	2700	3500
	BBC4008	8.0	3.0-5.0						
	BBC4010	10.0	4.0-6.5						
	BBC4012	12.0	6.0-8.5						
	BBC4014	14.0	7.0-10.5						
	BBC4016	16.0	8.0-12.5						
	BBC4018	18.0	10.0-14.5						
	BBC4020	20.0	12.0-16.0						
	BBC4025	25.0	16.0-21.0						
	BBC4030	30.0	21.0-26.0						
	BBC4035	35.0	26.0-30.5						
BBC4040	40.0	30.5-35.0							
4.8 +0.08 -0.15	BBC4806	6.0	1.0-2.5	8.3-9.5	2.0	3.1	4.9-5.0	4000	5000
	BBC4808	8.0	2.5-4.0						
	BBC4810	10.0	4.0-6.0						
	BBC4812	12.0	6.0-8.0						
	BBC4814	14.0	8.0-10.0						
	BBC4816	16.0	9.0-12.0						
	BBC4818	18.0	10.0-14.0						
	BBC4820	20.0	12.0-16.0						
	BBC4825	25.0	16.0-21.0						
	BBC4830	30.0	21.0-25.0						
	BBC4835	35.0	25.0-30.0						
	BBC4840	40.0	30.0-35.0						
	BBC4845	45.0	35.0-40.0						
	BBC4850	50.0	40.0-45.0						