


全铁开口型沉头抽芯铆钉 Steel/Steel CSK Head



Body:steel 铆体:铁
Mandrel:Steel 钉芯:铁

Body:Zinc Plated 铆体:镀锌
Mandrel:Zinc Plated 钉芯:镀锌



D	L			dk	k	dm			
RIVET SIZE	PART NUMBER	RIVET LENGTH	GRIP RANGE	HEAD DIA	HEAD HEIGHT	MANDREL DIA	HOLE SIZE (DRILL)	Shear (N)	Tensile (N)
		[+1/-0]	MIN-MIX		MAX.	MAX.	Φ	MIN.	MIN.
3.0 +0.08 -0.15	SSC3006	6.0	1.0-3.5	5.4-6.3	1.3	2.10	3.1-3.2	1000	1100
	SSC3008	8.0	3.5-5.0						
	SSC3010	10.0	5.0-7.0						
	SSC3012	12.0	7.0-9.0						
	SSC3014	14.0	9.0-11.0						
	SSC3016	16.0	9.0-12.5						
	SSC3018	18.0	12.0-14.5						
	SSC3020	20.0	13.0-16.5						
3.2 +0.08 -0.15	SSC3206	6.0	1.0-3.5	5.8-6.3	1.3	2.10	3.3-3.4	1100	1200
	SSC3208	8.0	3.5-5.0						
	SSC3210	10.0	5.0-7.0						
	SSC3212	12.0	7.0-9.0						
	SSC3214	14.0	9.0-11.0						
	SSC3216	16.0	9.0-12.5						
	SSC3218	18.0	12.0-14.5						
	SSC3220	20.0	13.0-16.5						
	SSC3225	25.0	15.0-21.5						
4.0 +0.08 -0.15	SSC4006	6.0	1.0-3.0	6.9-7.5	1.7	2.60	4.1-4.2	1700	2000
	SSC4008	8.0	3.0-5.0						
	SSC4010	10.0	4.0-6.5						
	SSC4012	12.0	6.0-8.5						
	SSC4014	14.0	7.0-10.5						
	SSC4016	16.0	8.0-12.5						
	SSC4018	18.0	10.0-14.5						
	SSC4020	20.0	12.0-16.0						
	SSC4025	25.0	16.0-21.0						
	SSC4030	30.0	21.0-26.0						
	SSC4035	35.0	26.0-30.5						
	SSC4040	40.0	30.5-35.0						
4.8 +0.08 -0.15	SSC4806	6.0	1.0-2.5	8.3-9.5	2.0	3.1	4.9-5.0	2900	3100
	SSC4808	8.0	2.5-4.0						
	SSC4810	10.0	4.0-6.0						
	SSC4812	12.0	6.0-8.0						
	SSC4814	14.0	8.0-10.0						
	SSC4816	16.0	9.0-12.0						
	SSC4818	18.0	10.0-14.0						
	SSC4820	20.0	12.0-16.0						
	SSC4825	25.0	16.0-21.0						
	SSC4830	30.0	21.0-25.0						
	SSC4835	35.0	25.0-30.0						
	SSC4840	40.0	30.0-35.0						
	SSC4845	45.0	35.0-40.0						
		SSC4850	50.0						